



Item	Description	Material	Item	Description	Material
1	Hose Braid	T-304 SS	3	Braid Band	T-304 SS
2	Hose	T-321 SS	4	Male Pipe Thread	ASTM A53 CS

Size (in)	L (in)	L1 (in)	L2 (in)	L3 (in)	D (in)	Pressure (PSIG) 70°F		Approx. Wt (lbs.)
						Operating	Test	
1/2	0.782	6.5	2.563	1.181	0.551	1040	1560	0.38
3/4	0.794	7	2.669	1.378	0.748	600	900	0.5
1	0.985	8	3.275	1.575	0.945	580	870	0.75
1-1/4	1.001	8.5	3.381	1.772	1.259	450	675	1
1-1/2	1.025	9	3.487	1.969	1.496	410	615	1.25
2	1.058	10.5	4.987	1.969	1.969	450	675	2.13

FNWTM

4120 NE Columbia Blvd
Portland, OR 97211
Phone (503) 287-8383
Fax (503) 281-9677

TITLE/DESCRIPTION: FNW METAL BRAIDED FLEXIBLE CONNECTOR WITH MNPT END CONNECTIONS

DATE: 8-8-2005 BY: UNITS: INCHES

SCALE: NONE APP'D: PAGE(S): 1

MODEL: 30T

DWG NO: FNW30T

NOTES:

FILE: 30T.dwg WT: LOC: PORTLAND

PAGE SIZE: 8.5 x 11L REV: 0 R'DATE:

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF FNW VALVE AND IS SUBMITTED TO YOU FOR THE LIMITED PURPOSE OF PROVIDING YOU INFORMATION ON PRODUCTS AND SYSTEMS PURCHASED FROM FNW VALVE. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION OF FNW VALVE.