



Ratings		
Working Pressure		200 PSI
Test Pressure	SHELL	300 PSI
	SEAT	220 PSI
Working Temperature	NBR	-4 °F to 194 °F
	EPDM	-22 °F to 230 °F

Ref. No.	Description	Material	Qty	Remarks
1	Retaining Plate	ASTM A283D-A36 STEEL	1	Galvanized
2	Retaining Plate Screw	ASTM A283D-A36 STEEL	2	Galvanized
3	Ingress Stem Seal	SAME AS SEAT MATERIAL	1	
4	Stem Bushing	PTFE	4	2 Upper, 2 Lower
5	Body	ASTM A536 65-45-12 DUCTILE IRON	1	
6	Upper Stem	416SS STAINLESS STEEL	1	
7	Seat	EPDM or BUNA	1	
8	Disc	JIS H 5114 ALUMINUM BRONZE	1	
9	Lower Stem	416SS STAINLESS STEEL	1	
10	Plug	ASTM A283D-A36 STEEL	1	
20	Gear Housing	ASTM A126 CAST IRON	1	
21	Gear Drive	ASTM A536 65-45-12 DUCTILE IRON	1	Not Shown
22	Gear Input Shaft	STEEL	1	Nickel Plated
23	Hand Wheel	ASTM A126 CAST IRON	1	
24	Gear Mounting Bolt	ASTM A283D-A36 STEEL	4	Zinc Plated

NOTE:
 1. Valve design in accordance with API 609A, MSS SP-67
 2. Testing in accordance with API 598, MSS SP-61
 3. The laying length of valve conforms to ISO 5752 PN 10/16 SHORT
 4. Dimensions for topworks conform to ISO 5211
 5. Dimensions for mounting flange conform to ANSI B16.1 150 PSI

Size	A	B	ØD	H1	H2	L1	G1	G2	H3	ØU	P	ØQ	ØS	T	ØV
10"	3.52	9.62	9.72	7.86	10.5	2.68	11.81	8.07	0.81	4.92	0.79	4.02	0.43	0.87	1
12"	4.28	11.54	11.63	9.47	12.15	3.07	11.81	8.46	0.95	4.92	0.79	4.02	0.79	0.87	1.1

FNW™

4120 NE Columbia Blvd
 Portland, OR 97211
 Phone (503)287-8383
 Fax (503)281-9677

TITLE/DESCRIPTION: Figure 711 Wafer Style Resilient Cartridge Seat 10" & 12" Lever Operated

DATE: 7-5-2012 BY: PEA NUMBER: 711_10-12

REV: 0 APVD: KMC

CONFIDENTIAL AND PROPRIETARY INFORMATION BELONGING TO FNW VALVE. SUBMITTED FOR THE LIMITED PURPOSE OF PROVIDING INFORMATION ON PRODUCTS AND SYSTEMS. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION OF FNW VALVE.