



Lug Patterns Vary by Valve Size

ØHxN on ØC b.c.

Ref. No.	Description	Material	Qty	Remarks
1	Retaining Plate	ASTM A283D-A36 STEEL	1	Galvanized
2	Retaining Plate Screw	ASTM A283D-A36 STEEL	2	Galvanized, 14"
			3	Galvanized, 16" & Up
3	Ingress Stem Seal	SAME AS SEAT MATERIAL	1	
4	Stem Bushing	PTFE	2	
4A	Upper Hard Bushing	ASTM B584 C83600 BRONZE	1	Sizes 14" -24"
4B	Lower Hard Bushing	ASTM B584 C83600 BRONZE	1	Sizes 14" -24"
5	Body	ASTM A536 65-45-12 DUCTILE IRON	1	
6	Upper Stem	ASTM A276 SUS 316 STAINLESS	1	
7	Seat	EPDM or BUNA	1	
8	Disc	ASTM A351 CF8M, STAINLESS	1	
9	Lower Stem	ASTM A276 SUS 316 STAINLESS	1	
10	Plug	ASTM A283D-A36 STEEL	1	Sizes 14" & 16"
11	Bottom Plate	ASTM A283D-A36 STEEL	1	Zinc Plated, Sizes 18"-24"
12	Bottom Plate Screw	ASTM A283D-A36 STEEL	4	Zinc Plated, Sizes 18"-24"
20	Gear Housing	ASTM A126 CAST IRON	1	
21	Gear Drive	ASTM A536 65-45-12 DUCTILE IRON	1	Not Shown
22	Gear Input Shaft	STEEL	1	Nickel Plated
23	Hand Wheel	ASTM A126 CAST IRON	1	
24	Gear Mounting Bolt	ASTM A283D-A36 STEEL	4	Zinc Plated

Ratings		
Working Pressure		188 PSI
Test Pressure	SHELL	282 PSI
	SEAT	206.8 PSI
Working Temperature	NBR	-4 °F to 194 °F
	EPDM	-22 °F to 230 °F

NOTE:
 1. Valve design and testing to be in accordance with API 609A, MSS SP-67 TYPE 1
 2. The laying length of valve conforms to ISO 5752 PN 10/16 SHORT, BS5155 PN 10/16 SHORT
 3. Dimensions for topworks conform to ISO 5211
 4. Dimensions for mounting flange conform to ANSI B16.1 150 PSI

Size	A	B	ØD	H1	H2	G1	G2	L1	ØC	ØH	N	H3	ØU	P	ØQ	ØS	ØT	W1	W2	X
14	4.96	12.83	12.99	10.41	13.60	11.81	8.46	3.07	18.75	1"-8	12	2.81	4.92	0.79	4.02	0.47	1.10	0.39	0.20	2.36
16	5.45	14.82	14.92	11.75	13.76	11.81	8.86	4.02	21.25	1"-8	16	3.15	6.89	0.91	5.51	0.71	1.26	0.39	0.20	2.36
18	6.36	17.09	17.20	13.78	15.75	15.55	8.86	4.49	22.75	1-1/8"-7	16	3.15	6.89	0.91	5.51	0.71	1.50	0.47	0.20	2.36
20	7.15	19.13	19.29	14.96	17.32	15.55	10.12	5.00	25.00	1-1/8"-7	20	3.54	8.27	0.91	6.50	0.87	1.77	0.47	0.20	2.76
24	8.28	22.46	22.62	17.32	20.08	15.55	10.12	6.06	29.50	1-1/4"-7	20	3.74	8.27	0.91	6.50	0.87	2.17	0.55	0.20	2.76

FNW™

4120 NE Columbia Blvd
 Portland, OR 97211
 Phone (503)287-8383
 Fax (503)281-9677

TITLE/DESCRIPTION
 Figure 732 Lug Style
 Resilient Cartridge Seat
 14" to 24" Gear Operated

DATE: 6-29-2012 BY: PEA NUMBER:
 REV: 0 APVD: KMC **732_14-24**

CONFIDENTIAL AND PROPRIETARY INFORMATION BELONGING TO FNW VALVE. SUBMITTED FOR THE LIMITED PURPOSE OF PROVIDING INFORMATION ON PRODUCTS AND SYSTEMS. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION OF FNW VALVE.

UNITS: INCHES SCALE: NTS PAGE 1 OF 1