



**NOTE:**

1. Valve design and testing to be in accordance with API 609A, MSS SP-67 TYPE 1
2. The laying length of valve conforms to ISO 5752 PN 10/16 SHORT, BS5155 PN 10/16 SHORT
3. Dimensions for topworks conform to ISO 5211
4. Dimensions for mounting flange conform to ANSI B16.1 150 PSI

Ref. No.	Description	Material	Qty	Remarks
1	Retaining Plate	ASTM A283D-A36 STEEL	1	Galvanized
2	Retaining Plate Screw	ASTM A283D-A36 STEEL	2	Galvanized
3	Ingress Stem Seal	SAME AS SEAT MATERIAL	1	
4	Stem Bushing	PTFE	2	1 Upper, 1 Lower, Sizes 2"-3"
			4	2 Upper, 2 Lower, Sizes 4"-12"
5	Body	ASTM A536 65-45-12 DUCTILE IRON	1	
6	Upper Stem	ASTM A276 SUS 316 STAINLESS	1	
7	Seat	EPDM or BUNA VITON®	1	
8	Disc	ASTM A351 CF8M, STAINLESS	1	
9	Lower Stem	ASTM A276 SUS 316 STAINLESS	1	
10	Plug	ASTM A283D-A36 STEEL	1	
13	Lever Stop Plate	ASTM A283D-A36 STEEL	1	
14	Lever	ASTM A47 Gr 32510 MALLEABLE IRON	1	
15	Lever Washer	ASTM A283D-A36 STEEL	1	Zinc Plated, Sizes 2"-8"
16	Lever Bolt	ASTM A283D-A36 STEEL	1	Zinc Plated, Sizes 2"-8"

Ratings		
Working Pressure		255 PSI
Test Pressure	SHELL	382 PSI
	SEAT	281 PSI
Working Temperature	NBR	-4 °F to 194 °F
	EPDM	-22 °F to 230 °F
	Viton®	-14 °F to 320 °F

**FNW™**

4120 NE Columbia Blvd  
Portland, OR 97211  
Phone (503)287-8383  
Fax (503)281-9677

**TITLE/DESCRIPTION**

Figure 732 Lug Style  
Resilient Cartridge Seat  
2" to 12" Lever Operated

DATE: 3-06-2017	BY: CA	NUMBER:
REV: 0	APVD: MC	<b>732_2-12</b>

CONFIDENTIAL AND PROPRIETARY INFORMATION BELONGING TO FNW VALVE. SUBMITTED FOR THE LIMITED PURPOSE OF PROVIDING INFORMATION ON PRODUCTS AND SYSTEMS. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION OF FNW VALVE.

UNITS: INCHES	SCALE: NTS	PAGE 1 OF 1
---------------	------------	-------------

Size	A	B	ØD	H1	H2	H4	L1	L2	ØC	ØH	N	H3	ØU	P	ØQ	ØS	T	ØV
2	0.18	1.93	2.05	2.77	4.94	1.06	1.69	11.37	4.75	5/8"-11	4	0.60	3.54	0.55	2.76	0.35	0.43	0.55
2-1/2	0.41	2.52	2.64	2.95	5.20	1.06	1.81	11.37	5.49	5/8"-11	4	0.60	3.54	0.55	2.76	0.35	0.43	0.55
3	0.67	3.03	3.15	3.67	6.07	1.06	1.81	11.37	6.00	5/8"-11	4	0.60	3.54	0.55	2.76	0.35	0.43	0.55
4	0.94	3.82	3.94	4.18	6.54	1.06	2.05	11.37	7.50	5/8"-11	8	0.70	3.54	0.63	2.76	0.35	0.55	0.63
5	1.36	4.80	4.92	4.69	7.13	1.06	2.20	11.37	8.50	3/4"-10	8	0.70	3.54	0.63	2.76	0.35	0.55	0.71
6	1.86	5.83	5.93	5.48	7.84	1.06	2.20	11.37	9.51	3/4"-10	8	0.70	3.54	0.63	2.76	0.35	0.55	0.71
8	2.69	7.62	7.74	6.51	9.26	1.06	2.36	17.83	11.75	3/4"-10	8	0.81	3.54	0.67	2.76	0.35	0.67	0.87
10	3.52	9.62	9.72	7.86	10.50	1.02	2.68	17.83	14.25	7/8"-9	12	0.81	4.92	0.79	4.02	0.43	0.87	1.00
12	4.28	11.54	11.63	9.47	12.15	1.02	3.07	17.83	17.00	7/8"-9	12	0.95	4.92	0.79	4.02	0.79	0.87	1.10