


GEAR-OP (8"~12")

TOPWORKS



FNW™

4120 NE Columbia Blvd
Portland, OR 97211
Phone (503)287-8383
Fax (503)281-9677

Material	Qty
ASTM A126 Gr. B CAST IRON	1
ASTM A126 Gr. B CAST IRON	1
NITRILE	1
POLYACETAL	1
ASTM A351 CF8M / SS316 SH STAINLESS STEEL	1

Material	Qty	Remarks
CARBON STEEL En8	2	Zinc Plated, Not Shown
CARBON STEEL	1	Zinc Plated
CARBON STEEL	1	2"~6", Powder Coated
SS304 STAINLESS STEEL	2	
CARBON STEEL	1	Zin Plated
CAST IRON	1	8"~12"
CARBON STEEL	1	8"~12", Fabricated
CARBON STEEL	4	8"~12", Zinc Plated

Size	H1	H2	H3	H4	L	L1	L2	ØG1	G2	P	P2	ØQ1	ØQ2	ØS1	ØS2	ØV	T	W	ØH (UNC)	N	ØC
2	2.76	5.51	0.63	1.22	1.81	1.63	10.23	-	-	0.39	3.15	-	2.76	-	0.39	0.56	0.43	6.10	5/8"-11	4	4.75
2-1/2	2.95	5.98	0.63	1.22	1.93	1.75	10.23	-	-	0.39	3.15	-	2.76	-	0.39	0.56	0.43	6.77	5/8"-11	4	5.50
3	3.35	6.30	0.63	1.22	1.93	1.75	10.23	-	-	0.39	3.15	-	2.76	-	0.39	0.56	0.43	6.89	5/8"-11	4	6.00
4	4.09	7.09	0.75	1.20	2.24	2.01	10.23	-	-	0.39	3.15	-	2.76	-	0.39	0.71	0.55	10.04	5/8"-11	8	7.50
5	4.72	7.56	0.81	1.54	2.36	2.15	13.85	-	-	0.45	3.94	2.76	4.01	0.39	0.47	0.87	0.67	10.63	3/4"-10	8	8.50
6	5.31	8.07	0.81	1.54	2.36	2.15	13.85	-	-	0.45	3.94	2.76	4.01	0.39	0.47	0.87	0.67	11.42	3/4"-10	8	9.50
8	6.69	9.49	0.94	2.52	2.78	2.49	-	9.84	9.84	0.49	4.72	4.01	4.92	0.47	0.55	0.99	0.75	13.78	3/4"-10	8	11.75
10	7.87	10.75	0.94	2.87	2.78	2.55	-	11.81	10.87	0.49	4.72	4.01	4.92	0.47	0.55	1.11	0.87	16.73	7/8"-9	12	14.25
12	9.06	12.24	1.14	3.11	3.25	2.99	-	17.71	13.19	0.49	4.72	-	4.92	-	0.55	1.43	1.06	19.50	7/8"-9	12	17.00

TITLE/DESCRIPTION
Figure 762
Teflon Seated Butterfly Valve Lugged
Drilled for ANSI Class 125/150# Flanges

DATE: 3-12-2013 BY: PEA NUMBER:
REV: 1 APVD: KMC **762_2-12**

CONFIDENTIAL AND PROPRIETARY INFORMATION BELONGING TO FNW VALVE. SUBMITTED FOR THE LIMITED PURPOSE OF PROVIDING INFORMATION ON PRODUCTS AND SYSTEMS. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION OF FNW VALVE.

UNITS: INCHES SCALE: NTS PAGE 1 OF 1