



Size	ϕD (IPB)		ϕO ± 0.112	T1	T2	T2 Tolerance	ϕB ± 0.068	ϕN ± 0.078	n	Wt (Lbc)
	B E ± 0.078	A F R ± 0.078								
1/2	0.90	-	3.50	0.25	0.500	± 0.079	2.375	0.625	4	-
3/4	1.11	-	3.88	0.25	0.500	± 0.079	2.750	0.625	4	-
1	1.375	1.750	4.25	0.25	0.500	± 0.079	3.125	0.625	4	1.1
1-1/2	1.969	2.375	5.00	0.25	0.500	± 0.079	3.875	0.625	4	1.7
2	2.437	2.750	6.00	0.25	0.500	± 0.079	4.750	0.750	4	2.9
2-1/2	2.937	3.250	7.00	0.25	0.500	± 0.079	5.500	0.750	4	3.8
3	3.563	4.000	7.50	0.25	0.500	± 0.079	6.000	0.750	4	4
4	4.563	5.125	9.00	0.25	0.500	± 0.079	7.500	0.750	8	5.3
6	5.625	6.063	10.00	0.25	0.500	± 0.079	8.500	0.875	8	7
8	6.750	7.250	11.00	0.25	0.625	± 0.079	9.500	0.875	8	8
8	8.750	9.375	13.50	0.25	0.625	± 0.079	11.750	0.875	8	11.4
10	10.875	11.375	16.00	0.25	0.625	± 0.079	14.250	1.000	12	14.1
12	12.875	13.625	19.00	0.25	0.750	± 0.079	17.000	1.000	12	23.8
14	14.187	14.750	21.00	0.25	0.750	± 0.118	18.750	1.125	12	30.9
18	16.187	16.880	23.50	0.25	0.750	± 0.118	21.250	1.125	16	40
18	18.187	18.750	25.00	0.25	0.750	± 0.118	22.750	1.125	16	43.5
20	20.250	20.750	27.50	0.25	0.875	± 0.118	25.000	1.125	20	53
24	24.250	24.750	32.00	0.25	1.000	± 0.157	29.500	1.375	20	80
30	30.375	30.875	38.75	0.25	1.000	± 0.157	36.000	1.375	28	104
38	36.500	36.875	45.50	0.25	1.125	± 0.157	42.750	1.625	32	150

MATERIAL
ASTM A536 grade 65-45-12

PHYSICAL PROPERTIES (MINIMUM)
TENSILE STRENGTH: 65,000 PSI
YIELD STRENGTH: 45,000 PSI
ELONGATION: 12%

FINISH
RED PRIMER PAINT
OR
HOT DIPPED GALVANIZED



TITLE: FNW IPS DUCTILE IRON BACK-UP FLANGES

DATE: 2-182008

BY: PEA

APP'D: KMC

UNITS: IN

SCALE: NONE

FILE: FNWDIBUF 050-36.dwg

MODEL: VARIOUS

DWG NO: FNWDUBUF

REV: 1

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF FNW VALVE AND IS SUBMITTED TO YOU FOR THE LIMITED PURPOSE OF PROVIDING YOU INFORMATION ON PRODUCTS AND SYSTEMS PURCHASED FROM FNW VALVE. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION.